

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 June 2001 (14.06.2001)

PCT

(10) International Publication Number
WO 01/42894 A1

(51) International Patent Classification⁷: G06F 3/00, 17/30

(21) International Application Number: PCT/SE00/02517

(22) International Filing Date:
13 December 2000 (13.12.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
9904552-8 13 December 1999 (13.12.1999) SE
60/198,531 19 April 2000 (19.04.2000) US

(71) Applicant (for all designated States except US): AXIS AB
[SE/SE]; Scheelevägen 34, S-223 63 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LARSSON, Olof
[SE/SE]; Luzernvägen 12, S-227 38 Lund (SE). FAGER-
BERG, Lennart [SE/SE]; Vallmostigen 2, S-240 13
Genarp (SE).

(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö
(SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AT
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility
model), DK, DK (utility model), DM, DZ, EE, EE (utility
model), ES, FI, FI (utility model), GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK
(utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR PRESENTING INFORMATION



(57) Abstract: A presentation of a selected document, stored at a node of a network, is accomplished by means of a system essentially comprising a handheld device, a communication device for a presentation unit and a device that handles presentation requests. By operating the handheld device, a user is able to get a presentation unit specification from said communication device. This specification is then sent, together with an address to a selected document, to a device handling presentation requests. In this device the selected document is then converted to a format suitable for the presentation unit of said communication device, where the converted document is presented. The system could be using WAP-technology for sending information from the handheld device to the device that handles presentation requests and for accessing information on the Internet. Further the system could, for example, be using Bluetooth or IrDA for the communication between the handheld device and said communication device. The system also makes it possible to achieve mobile printing and portable access to documents that cannot be presented on a small display.

METHOD AND SYSTEM FOR PRESENTING
INFORMATION

Technical Field of the Invention

The present invention relates to a system and methods for presenting electronically stored information on a presentation unit via a network.

Background of the Invention

Today a lot of information is accessible over networks such as Intranets and the Internet. Even information that is to be accessible only for a specific group of users can be accessed over these networks by means of secure communication channels and different identification methods.

To have information presented on a presentation unit nearby, the user must have a computer having access to the network in which the information is accessible and a presentation unit connected to the computer. Thus, people that travel a lot and need access to information stored on, for example, a company server have to carry with them a computer to be able to access the desired information. Further, they either have to have a portable modem with them or have access to a network connection.

The access to information can be accomplished by means of a cellular telephone implementing e.g. the Wireless Application Protocol (WAP), a Personal Digital Assistant (PDA) or a similar device. Then, the user has access to information presented in a format presentable on the cellular telephone. However, if the information is a text document comprising a large amount of text, e.g. a patent application, or a blueprint of a machine to repair, then it is not suitable and often not even possible to present the information on the cellular telephone. Even if the telephone is capable of using a

normal Internet Protocol (IP) connection for communication, the information has to be adapted to the small size screen of the telephone or the PDA, and thus it would be very difficult for the user to get an
5 overview or even read such a document.

Summary of the Invention

The object of the present invention is to make it possible for a person to have information presented to
10 him in a form that is easy to read and overview, even if the information is in a form not suitable for easy reading on a small display.

Another object is to increase the mobility of people who require access to information of the above-mentioned
15 character.

Yet another object is to make it possible for a person to access documents that are electronically stored at a remote location.

These objects are accomplished by means of a method
20 in a system according to claim 1, a system according to claim 6, a method for a device that handles presentation requests according to claim 12, a device that handles presentation requests according to claim 20, a computer program product according to claim 26, a method for a
25 communication device according to claim 27, a communication device according to claim 33, a method for a handheld device according to claim 36, or a handheld device according to claim 39. Preferred embodiments of the invention are disclosed in the dependent claims.

30 More particularly, according to one aspect of the invention, a method in a system for selection and presentation of information, comprises the steps of:

receiving a presentation unit identification at a handheld device via a short-range wireless connection
35 from a communication device for a presentation unit,

sending a document address from the handheld device via a network to a device that handles presentation requests,

receiving said document address and a presentation unit specification at the device that handles presentation requests,

retrieving, at the device that handles presentation requests, the document corresponding to said document address,

converting, at the device that handles presentation requests, the retrieved document to a format suitable for the presentation unit,

sending the converted document from the device that handles presentation requests via a network to the communication device for a presentation unit, and

receiving said converted document at the communication device for a presentation unit.

According to another aspect of the invention, a system for selection and presentation of information, comprises:

a handheld device, enabled to present information retrieved from an information provider on a screen in the handheld device, including:

an I/O-interface for short-range wireless communication with a communication device for a presentation unit,

means for receiving a presentation unit identification via said I/O-interface for short-range communication,

means for sending a document address to a device that handles presentation requests, and a device that handles presentation requests, including:

means for receiving a document address, referring to a document that is to be presented, from a handheld device,

means for receiving a presentation unit specification,

means for retrieving the document corresponding to the document address,

5 means for converting the retrieved document to a format that is suitable for the presentation unit according to the presentation unit specification, and

10 means for sending the converted document to the presentation address,

a communication device for a presentation unit, including:

an I/O-interface for short-range wireless communication with a handheld device,

15 means for sending a presentation unit identification via said I/O-interface for short-range wireless communication, and

means for receiving information to be presented by a presentation unit.

20 The system according to the invention solves the problems accounted for above. When the need for a certain document arises, a user of this system only has to pick up his handheld device, make it display a page where the document is identified, select the desired document on
25 said page for presentation on the presentation unit, make it identify a communication device for a presentation unit nearby, and then have the document presented on said presentation unit. The document can be located at any node of a network as long as there is an address
30 identifying it. The address to the document is sent from the handheld device to a device that handles presentation requests, a specification of the presentation unit is sent either from the handheld device or from the communication device of the presentation unit to the
35 device that handles presentation requests, and then the document will be sent to the presentation unit in a format that the presentation unit understands.

The system is advantageous by being able to allow essentially any kind of document to be presented on essentially any kind of presentation unit. Further, the system provides this advantage without requiring any additional memory in the handheld device or the communication device for the presentation unit for storing conversion means for various document formats and presentation units. This is achieved by having the requested document converted in a device that handles presentation requests.

Another advantage of performing the conversion in the device that handles presentation requests is that the normal operation neither of the handheld device nor of the communication device is affected negatively by the conversion.

Yet another advantage of performing the conversion in a device that handles presentation requests is that the document does not necessarily need to be sent to the handheld device, at least not before it is converted. This is achieved by making the device that handles presentation requests retrieving a requested document on the basis of a document address received from the handheld device, and therefore the handheld device only needs to communicate the document address in order to make the document available to the device that handles presentation requests. Thus, by having the device that handles presentation requests retrieving the document, bandwidth is saved on the communication paths of the handheld device.

A further advantage of performing the conversion at the device that handles presentation requests, and thus positioning the means for conversion at this location, is that the process of adding new means for conversion or changing of old means for conversion is simplified to a great extent. One reason therefor is that there will be a greater number of handheld devices or presentation units than devices that handle presentation requests, whereby

it will be easier for an administrator to perform an upgrade of the conversion means at the device that handles presentation requests. Another reason is that the handheld device is probably not connected to a network all the time. Thus, a user should be required to personally perform an update of conversion means if the means were located in the handheld device.

The system is also advantageous in that the handheld device is able to exchange data with presentation units nearby and can also be made to identify them, thanks to the short-range communication link. Thus, a user does not need to worry about manually identifying a presentation unit and typing in data needed to utilise the presentation unit. As a result, the user is not required to search for parameters needed to accomplish a presentation. These advantages are accomplished by means of the short-range communication link that is established between the handheld device and a communication device for the presentation unit. The short-range communication link can for example be implemented using Bluetooth, IrDA, Open Air, Home RF, Hiper Lan, IEEE 802.11, etc.

In the context of the invention, a presentation unit represents devices that are able to present electronically represented information that cannot be presented satisfactorily on a small display of a handheld device. The presentation unit could be, for example, a screen, a rather large display, an e-book, an electronic picture frame or a printer.

According to a preferred embodiment of the invention, the presentation unit is a device that creates a copy of an electronic document on or in a medium that is highly portable. In that case, a presentation unit could, for example, be a conventional printer or an electronically controllable presentation medium, e.g. e-books, electronic picture frames, etc.

In a preferred embodiment the presentation unit is a printer. By presenting the information via a printer on a printable medium, it is possible to have information presented in high resolution and it is easy get an
5 overview of the information. Another advantage of using a printer as presentation unit is that a printed document format is well known and easy to utilise for essentially any person and that a printed document is easy to add comments to or sign, which still is required in regard of
10 most contracts.

An information service provider is a system that allows access to browsable information on a network, e.g. electronically stored documents, e-mails, drawings, blueprints etc. The information service provider could,
15 for example, be an Internet portal or a server for serving the documents of a company to employees or other people allowed access to them. The server for serving the documents of a company could, for example, be a system such as a unified messaging server.

20 A handheld device is a device that is enabled to communicate over a network and to display information found at nodes of a network, at least in the form of text but preferably also in the form of pictures. Further, it is preferably of such size that a user could hold it in
25 one hand while operating it with the other. The device could for example be a cellular telephone, a PDA or a small computer. In a preferred embodiment, the device is provided with a browser for presenting and browsing the information available on the network.

30 In the context of the invention a network is, for example, a communication network for telephones, a Wide Area Network (WAN), a Local Area Network (LAN), the Internet or an Intranet.

In one preferred embodiment of the invention the
35 search or selection of information is performed from the handheld device via a wireless telephone network and a station of the network operator giving the handheld

device access to an information service provider, which could be directly accessed at the station or could be accessed via a network. In this embodiment the handheld device is a cellular telephone and the user can search
5 for information as long as the telephone is able to establish contact with the network of the telephone operator. The embodiment has the advantage of making the information available at almost any location, allowing the user to search for a document to present wherever he
10 may be. Then, when a document is found, the user can move to a location where the short-range communication link can be established between the telephone and a communication device for a presentation unit for presentation of the document.

15 In another preferred embodiment of the invention the search or selection of information is performed from the handheld device via the short-range communication link and the communication device for the presentation unit. In this embodiment the communication device is providing
20 an access point to the Internet, an Intranet or another computer network, from which the information service provider can be accessed. The handheld device of this embodiment could, for example, be a PDA or a small computer. The advantage of this embodiment is that the
25 handheld device does not need any other connection than the short-range communication link for searching or selecting information.

According to a preferred embodiment, the device that handles presentation requests is a module in an
30 information service provider. By providing the device that handles presentation requests as a module in an information service provider, the device is able to share functionality and interfaces with the information service. Further, if the information service provider
35 serves confidential information, the security of the document for presentation is easily maintained.

The system can utilise different paths for sending the presentation file, which is the requested document converted to a suitable format. It is possible to manufacture devices supporting all of the paths or only one or some of the paths. Thus, the paths from the device that handles presentation requests to the presentation unit described below can all be supported by one device.

In one preferred embodiment of the invention, the presentation file is sent from the device that handles presentation requests to the communication device for the presentation unit via at least a wireless network for cellular telephones, the handheld device, and the short-range communication link. One advantage of this embodiment is that the presentation file can be sent to the presentation unit even if the communication device for the presentation unit is lacking a network connection. Another advantage is that the path for the sending of the presentation file has already been established, during the selection of document and presentation unit, and thus the user can be certain that there is a path for sending the presentation file to the presentation unit.

In another preferred embodiment of the invention, the presentation file is sent from the device that handles presentation requests to the communication device for the presentation unit via a network such as the Internet and/or an Intranet. An advantage of this embodiment is that the data rate of the transmission is very high. Another advantage of this embodiment is that the user is able to use the handheld device to perform other tasks when waiting for the presentation.

In yet another preferred embodiment of the invention, the presentation file is sent from the device that handles presentation requests to the communication device for the presentation unit by e-mail. Advantages of this embodiment are that there is no trouble in presenting a presentation file on a presentation unit

that is located behind a firewall and that the data rate of the transmission is very high. According to one embodiment, the e-mail containing the presentation file is sent to a mail server handling the e-mails addressed to the presentation unit. Then, either the mail server sends a notice to the communication device regarding the newly received e-mail or the communication device frequently checks the mail server for new mails.

According to one aspect of the invention, a presentation of a selected document, stored at a node of a network, is accomplished by means of a system essentially comprising a handheld device, a communication device for a presentation unit and a device that handles presentation requests. By operating the handheld device, a user is able to get a presentation unit specification from said communication device. This specification is then sent, together with an address to a selected document, to a device handling presentation requests. In this device the selected document is then converted to a format suitable for the presentation unit of said communication device, where the converted document is presented. The system could be using WAP-technology for sending information from the handheld device to the device that handles presentation requests and for accessing information on the Internet. Further the system could, for example, be using Bluetooth or IrDA for the communication between the handheld device and said communication device. The system also makes it possible to achieve mobile printing and portable access to documents that cannot be presented on a small display.

Additionally, the communication device for a presentation unit could be arranged to receive simple information files stored in the handheld device via the short-range communication and to pass the simple information files to the presentation unit. Such files could, for example, be text files comprising the information of a WAP-page, a list of telephone numbers,

an address list, etc. To initiate the sending of such information for presentation, the handheld device is provided with a "present" or a "print" command in one of its menus and could also be provided with a button
5 dedicated to performing this action.

A further scope of applicability of the present invention will become apparent from the detailed description given below. However, it should be understood that the detailed description and specific examples,
10 while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

15

Brief Description of the Drawings

Other features and advantages of the present invention will become apparent from the following detailed description of a presently preferred embodiment, with
20 reference to the accompanying drawings, in which

Fig. 1 is a schematic view of a preferred embodiment of the invention,

Fig. 2 is a schematic view of a preferred embodiment of the invention utilising one preferred communication
25 device for a presentation unit,

Fig. 3 is a schematic view of a preferred embodiment of the invention utilising another preferred communication device for a presentation unit,

Fig. 4 is a schematic view of a preferred embodiment
30 of the invention utilising yet another preferred communication device for a presentation unit,

Fig. 5 is a schematic view of a device that handles presentation requests according to a preferred embodiment of the invention,

35 Fig. 6 is a schematic view of a handheld device according to a preferred embodiment of the invention,

Fig. 7a is a schematic view of one embodiment of a communication device for a presentation unit,

Fig. 7b is a schematic view of another embodiment of a communication device for a presentation unit,

5 Fig. 8 is a flowchart of a process in the handheld device according to a preferred embodiment of the invention,

10 Fig. 9 is a flowchart of a process in the device that handles presentation requests according to a preferred embodiment of the invention,

Figs 10a and b are flowcharts of a process in the communication device for a presentation unit in a preferred embodiment of the invention,

15 Fig. 11 is a diagram over signals sent between different units of the system according to one embodiment of the invention,

Fig. 12 is a schematic view of one embodiment of the invention, in which the information service provider handles e-mails, and

20 Fig. 13 is a flowchart of a process for printing e-mails and e-mail attachments by means of a handheld device.

Detailed Description of a Presently Preferred Embodiment

25 In Fig. 1, there is shown a preferred embodiment of a document presentation system. The system comprises at least one cellular telephone 100, at least one information service provider 200 and at least one communication device 300, in Fig. 1 represented by 300a and 300b, for a presentation unit.

30 The cellular telephone 100 is connected to a network 10, e.g. Internet, Intranet, Wide Area Network (WAN), Local Area Network (LAN), via a wireless network 14, e.g. a GSM-network, a TDMA-network, or another wireless network for cellular telephones, and a station 12 of a network operator providing wireless
35 access to the network 10. The access to the network 10 is accomplished by providing the station 12 with a gateway

implementing, for example, the Wireless Application Protocol (WAP), Hyper Text Transport Protocol (HTTP) or some other protocol for communicating information over a wireless telephone network. Further, the cellular
5 telephone 100 is provided with an interface for short-range wireless communication, such as Bluetooth.

The information service provider 200 is either directly connected to the station 12 or connected to the network 10. However, the information service provider 200
10 should have some access to a network 10. The information service provider 200 is either an Internet portal or a server for serving the documents of a company, and is providing access to documents, e-mails and/or other browsable information on the network in a format suitable
15 for the telephone 100. A print service device 210 is preferably built into the information service provider 200, but could also be positioned externally from the information service provider 200. The print service device 210 is a device that handles the request
20 of a document to be printed and is preferably implemented as a software code executed in the information service provider.

The communication devices 300a,b are connecting printers 380 to the network 10. A communication device
25 could, for example, be implemented in a print server. It can be connected to a printer either as an external device 300a, as an internal device 300b or as an embedded device 300b. It is provided with an interface for short-range wireless communication, such as Bluetooth. The main
30 tasks of the communication devices 300a,b are to make sure that a print file sent to one of the communication devices for printing is printed and to provide a cellular telephone with a printer specification. In another embodiment the communication device receives a document
35 address from the cellular telephone and then the communication device transmits the document address and the printer specification to the information service

provider. The printer specification comprises data regarding the transport route for a print file that is to be printed, the characteristics of the printer, and is described in more detail below.

5 The transport route of a print file between the printer service device 210 and the communication device 300a,b can be of different types, depending on what kind of communication device that is arranged to receive the print file. One route is to send the print
10 file directly to one of the communication devices 300a,b over the network 10 using IP protocols. For this purpose a File Transfer Protocol (FTP), an Internet Printing Protocol (IPP), etc can be used. Another route is to send the print file in an e-mail, for example by means of SMTP
15 or IMAP, to an e-mail address dedicated to a chosen communication device 300a,b. The e-mail is then routed to an e-mail server 390, which provides the chosen communication device 300a,b with the print file. Yet another route is to send the print file back to the
20 cellular telephone 100, for example by means of IP and/or WAP Protocols, e.g. as Wireless Session Protocol (WSP), and via the interface for short-range communication 20 transmit the print file to the chosen communication device 300a,b.

25 In Figs 2,3 and 4 said different communication device implementations are shown. The figures also show more details of one embodiment of the invention, e.g. the network is described as the Internet 11 and the site of the printer is surrounded by a frame 50 that defines the
30 nearby surroundings of the printer. The nearby surroundings of the communication device 300 shall, in this embodiment, be seen as a LAN of a company that is restricted to an office or a building, or a zone in which the short-range communications 20 of a telephone 100 can
35 be received by the communication device 300. As illustrated in Figs 2 and 3 a company LAN that is connected to the Internet is usually connected thereto

via a security system such as a firewall 52 in order to reduce the risk of unauthorised access to the LAN.

Further, there are shown three possible information

service providers 200a-c, generally referred to as 200,

5 one provided by the operator at the station 12, one

provided as an internet portal 62, and one provided by a

company 60 for serving company documents to employees. In

all three figures, the procedure for requesting a

document to print can be the same, only with a variation

10 of the data in the specification in accordance with the

present communication device implementation.

Fig. 2 shows the communication device implementation

that receives the print file as an e-mail. The e-mail is

sent from one of the print service devices 210a-c,

15 generally referred to as 210, to an e-mail server 390 via

the Internet 11, the firewall 52, and finally a LAN. When

the print file comprised in the e-mail is received at the

mail server 390, it is transmitted to the communication

device 300 for printing. By using an e-mail as a carrier

20 of the print file, a possible problem of getting the

print file through the firewall 52 is avoided.

Fig. 3 shows the communication device implementation

that receives the print file directly from one of the

print service devices 210a-c via the Internet, the

25 firewall, and a network connection, which could be either

a LAN or a single Internet access point. In this

embodiment the print file is addressed direct to the

communication device 300.

Fig. 4 shows the communication device implementation

30 that receives the print file from one of the print

service devices 210a-c via at least the wireless

telephone network 14, the telephone 100 and the short-

range communication link 20. In this embodiment the print

file does not need to be sent over the Internet if the

35 print service device 210a positioned at the site of the

operator is utilised, but the Internet could be used if

suitable. This communication device implementation is

preferred if there is no network connection or if there is other reasons for not connecting the communication device to a network.

Now referring to Fig. 5, an embodiment of a print service device 210 is shown. The print service device 210 is provided with means 212 for receiving a request for a document to be printed. The request comprises a document address, indicating where the document is situated, and a printer specification. The printer specification comprises, for instance, information regarding how to send the print file to the printer and the manufacturer and the model of the printer; further details will be described below. The request is passed from the means 212 for receiving a request to a control means 214. The control means 214 then extracts the document address from the request and passes it on to a means for retrieving documents 216.

The means for retrieving documents 216 then retrieves the document from the specified address within a memory 230 that the information provider has access to. The memory 230 could be a storage memory of the information service provider or any memory connected to and accessible via a network such as the Internet or an Intranet. The control means 214 passes the retrieved document and a portion of the printer specification containing data for selecting an appropriate device driver 220 to a document conversion means 218.

The document conversion means 218 checks the retrieved document to find out the format in which the document has been saved. The most simple method for checking the format is to read and interpret the file extension, e.g. ".txt" for a plain text file, ".doc" for a Microsoft® Word file, ".pdf" for an Acrobat® Reader file, ".tif" for a Tagged Image File, ".ps" for a postscript file, ".dwg" for a AutoCad® file, etc. However, only checking the extension of the file is a rather uncertain method for learning the format, because

the extension could be wrong or another program could use the same extension. Therefore, in a preferred embodiment, also the contents of the file are checked for portions indicating the format of the file. When the document
5 format has been determined, the document conversion means 218 selects a corresponding application 224 for interpreting the document. The applications 224 could be a program dedicated to interpret one or a plurality of formats, or it could be a full version of a program that
10 is even able to create documents of the present format.

Further, the document conversion means 218 uses a portion of the printer specification containing data for selecting an appropriate device driver 220 to determine what device driver 220 to use for creating the print
15 file. The determination can be based on data defining the manufacturer and the model of the printer and/or the Plug and Play (PnP) device ID of the printer.

The conversion means now utilises the selected application 224 and the selected device driver 220 to
20 convert the requested document to a printer file that the target printer can use.

The control means 214 also checks the printer specification for the route that the print file is to be sent. For example, the specification could contain an e-
25 mail address, the IP-address of the communication device, or a return address to the cellular telephone.

The control means 214 provides a send print file means 222 with the information of the route, e.g. an address, and the print file. Then the send print file
30 means 222 sends the print file to the target printer via the requested route.

Now referring to Fig. 6, there is shown a cellular telephone 100 arranged to request and receive a presentation unit specification via a short-range
35 communication link 20 and to send a document request via a wireless telephone network. The cellular telephone is a WAP-enabled cellular telephone provided with a user

interface 110 comprising a touch screen or a display and a keypad. The user interface is connected to an information browser means 112, which, in accordance with the WAP-standard, browses information on a network in response to events at the user interface 110. The information browser is implemented as a program that is processed by a Central Processing Unit (CPU) 114. The communication via the short-range communication link is provided by means of a short-range communication interface 116, preferably implementing Bluetooth, connected to the CPU 114. For the communication over the wireless telephone network 14, the cellular telephone is provided with an ordinary interface 118 for a cellular telephone.

Reference is now being made to Figs 7a and 7b, showing two embodiments of a communication device 300 according to the invention. Both embodiments of the communication device 300 are provided with a Central Processing Unit 302 (CPU) for handling the processes of the communication devices 300. They are also provided with an interface 304 for communication via a short-range communication link 20 and an interface 306 for connecting a printer 380. The communication device 300 according to Fig. 7a is arranged to receive print files via the short-range communication link 20, in accordance with the route of Fig. 4. The communication device 300 according to Fig. 7b is arranged to receive print files via the network 10, in accordance with the routes of Fig. 2 or Fig. 3. Therefore, the communication device 300 of Fig. 7b is provided with an additional interface 308 for communication over the network 10. Both embodiments of the communication device 300 are provided with protocols for communication via the interfaces of each communication device 300.

The primary object of the printer specification provided to the print service device via the telephone is to identify what formats the printer is able to print and

to identify what route the file has to be sent to get to the printer. For these purposes, the print file comprises data regarding the manufacturer and the model of the printer and an address to which the print file is to be sent. The printer specification could, for example, be a text file like the one presented below:

```
<?xml version='1.0' standalone='yes'?>
<MobilePrint0.1>
10  <PrinterManufacturer></PrinterManufacturer>
    <PrinterModel></PrinterModel>
    <PrinterPnPID></PrinterPnPID>
    <PrinterID></PrinterID>
    <PrinterDeviceDriverURL></PrinterDeviceDriverURL>
15  <PrinterEmailAddress></PrinterEmailAddress>
    <PrinterHostName></PrinterHostName>
    <PrinterIPAddress></PrinterIPAddress>
    <PrinterIPPURL></PrinterIPPURL>
    <PrinterPDLs></PrinterPDLs>
20  <PrinterLocalName></PrinterLocalName>
    <PrinterComment></PrinterComment>

</MobilePrint0.1>
```

25 In the specification above, the data of, for example, the printer manufacturer is to be positioned between the <PrinterManufacturer> and the </PrinterManufacturer>.

Now assume that a travelling service technician is travelling around the world servicing and repairing industrial robots. During an assignment he encounters a malfunction in a robot he is not very familiar with. He then needs the documentation of the robot. To get the documentation he asks for a printer having a Printer Server according to a preferred embodiment of the invention. He could also use his cellular telephone and instruct it to check the nearby surroundings for a communication device that is providing the service according to the invention.

Now referring to Figs 1 and 8, when the service technician locates a communication device 300, he uses his WAP-enabled cellular telephone 100 to connect, step

510, to an operator that provides a WAP-gateway 12 to the Internet 10. Then a WAP-page is presented, step 512, on the display of the telephone 100 from which he can browse a web of linked WAP-pages by selecting links, 514, presented on the display. Every time a link is selected, the telephone 100 checks if the link is pointing at another WAP-page or not, step 516. If the link points at another WAP-page, that page is downloaded and presented on the display, step 512, and the procedure is repeated, steps 512-516. A known WAP-page is also possible to get to by having the address of it stored in the telephone 100 and then selecting it or simply by typing the address in the information browser of the telephone 100.

In one of the above-mentioned ways, the service technician gets an information page containing a link to the document he needs presented, step 512. Now, he selects the link to the document, step 514, which is not a WAP-page. The telephone 100 checks if the link is pointing at a WAP-page, step 516, and finds out that it is not. Then the telephone 100 presents a print/download dialog, step 518. If the service technician selects download, the document could be downloaded, step 522, to a computer nearby, for example via the short-range communication link. However, if he selects print, the telephone 100 will broadcast an identity request via the short-range communication interface to all communication devices 300 within reach of the telephone 100 in regard of short-range communication 20, step 524. If there is no response to the request, an error message is presented in the display, step 528, indicating that there is no compatible communication device 300 available. Then the telephone 100 returns to step 512 and presents the WAP-page again. If there is one or more communication devices 300 responding to the request, the communication devices 300 are presented on the display, step 530. Then the service technician is enabled to select one of the

communication devices 300 displayed, step 530. When one communication device 300 is selected, the telephone 100 sends a request to the selected communication device 300 for a printer specification, step 534. The communication
5 device 300 returns a printer specification which is received at the telephone 100, step 536. Then a print request comprising a document address, given by the selected link, and the printer specification is sent to a print service device 210 of an information service
10 provider 200, step 538, via the wireless telephone network 14.

Now referring to Figs 1 and 9, the print request is received at a print service device 210, step 602. The device 210 identifies the different parts of the request,
15 step 604, e.g. one document address and one printer specification, and uses the document address to retrieve the document that is to be printed, step 606. Then the format of the retrieved document is identified, step 608, as described above. When the format of the document is
20 established, the print service device 210 uses this information and the presentation unit specification in the request to find an appropriate application for interpreting the document and a device driver, corresponding to the information of the printer
25 specification, for converting the document to a print file suitable for the selected printer, step 610. Then the document is converted to a print file, step 612.

The print file is now ready to be sent to the selected communication device. However, before the print
30 file is sent, the print service device selects a transmitting method in accordance with an address given in the printer specification, step 614. Thereafter the print file is sent to the communication device via one of the routes described above, step 616.

35 Now referring to Figs 1 and 10a, if the communication device 300 is arranged to receive print files via the telephone 100 and the interface for short-

range communication 20 or directly via the Internet 10, then the communication device 300 receives the print file, step 702, and passes it to the printer for printing, step 704.

5 Now referring to Figs 1 and 10b, if the communication device 300 is arranged to receive print files via e-mail, then the communication device could check the mail server 390 at predefined time intervals, step 712. If a new mail is present, step 714, then the
10 communication device 300 retrieves the e-mail, step 716, and thereafter extracts the print file from the e-mail, step 718. When the print file is extracted, it is passed to the printer 380 for printing, step 720.

15 Now the service technician can pick up the document from the printer and begin repairing the robot.

 With reference to Fig. 11, an example of communication between devices of the system and between the cellular telephone and a user is presented. The user initiates the WAP-browser of the cellular telephone,
20 event 902. Then he makes the telephone connect to an information service provider, event 904. The telephone sends a connect request 906 to the information service provider. In response the information service provider sends an authentication request 908 to the telephone for
25 authentication of the user. The user types a PIN-code into the telephone, event 910, and the telephone passes the PIN-code and a SIM-code of the subscriber to the information service provider as an authentication message
30 912. When the information service provider has accepted the user, it sends an initial WAP-page 914 to the telephone. The user is then able to select links on the pages presented on the telephone for browsing the information of the information service provider, event
35 916. During the browsing the telephone requests pages according to selected links while the information provider responds to the request by sending the requested pages; this corresponds to the bi-directional

communication of 918. When the user selects a link to a document that is not a WAP-page, event 920, the telephone presents a print dialog, event 922. If the user chooses to initiate printing, event 924, the telephone broadcasts
5 a message 926 via the short-range communication interface, implementing for example Bluetooth, to all communication devices that are capable of acting as a communication device for the present invention. Said communication devices then respond to the request by
10 sending a message 928, comprising identification information, to the telephone. The user is then prompted to select one of the identified communication devices from a list, if there are more than one responding. If only one is identified, the user has to select that one
15 or abandon the operation. When a communication device is selected, the telephone sends a request 932 for a printer specification to the selected communication device. The selected communication device responds by returning the printer specification 934 to the telephone. Thereafter
20 the telephone sends a request 936, comprising the printer specification and the document address, to the information service provider regarding printing the document at the specified printer. The request is passed 938 to the print service device of the information
25 service provider for conversion of the document to a printable format and for sending the converted document to the selected printer. When the document is converted and if no errors occur, the print service device sends the print file 940 to the communication device, for
30 example via e-mail. When the print file is sent, the information service provider gets a message 942 that the conversion was successful. If the conversion failed, the information provider gets a message 942 that the conversion failed. The message is passed along 944 to the
35 telephone that presents it to the user.

The invention could also be used to facilitate reception of e-mails at handheld devices. Today it is

possible to receive e-mails in your PDA or mobile telephone via, for example, Short Message System (SMS), WAP, i-mode, etc. However, the handheld devices are provided with limited recourses regarding, for example, CPU performance, memory size, and resolution and size of the display. Thus, it is difficult, if possible at all, to view complex or large e-mail attachments in handheld devices having such limited resources.

In Fig. 12 an information service provider 200 according to one embodiment of the invention is shown. The information service provider 200 of this embodiment is arranged to administrate e-mail accounts and e-mails sent to e-mail addresses of said e-mail accounts. The information service provider of this embodiment is arranged to receive e-mails, store the e-mails and attachments accompanying the e-mails, and present, on request, the stored e-mails of an account to a person having permission to view the e-mails of the account.

When receiving an e-mail, said information service provider 200 stores the text of the e-mail in an e-mail storage means 232, it stores the attachment/attachments, if any, in an attachment storage means 234, and it registers a pointer to every attachment included in the mail at the text of the stored e-mail. In a preferred embodiment of the invention the pointer to the attachment is an address such as a Uniform Resource Locator (URL). If the pointer to an attachment is an URL it may, for example, have the following appearance:

<http://www.abcd.com?id=12345&key=12345>

When receiving a request for presentation of an e-mail, said information service provider 200, sends a presentation of the text of the requested e-mail to the handheld device 100 from which the presentation was requested. The presentation of the text that is sent does not include any attachments, but does include a pointer

to the attachment / attachments belonging to the e-mail. Then the user is able to get an attachment presented at a presentation unit 380 nearby by means of the handheld device 100 by utilizing any technique previously
5 described in this document.

In order to print the entire mail, including attachments, the handheld device 100 comprises a menu or a presentation button, which initiates the above-mentioned process for presentation of information. In
10 response to a request for printing of the entire e-mail, currently viewed in the handheld device or referred to on a display of the handheld device 100 by means of a pointer or a link, the handheld device 100 checks the contents of the e-mail and sends the addresses of the e-
15 mail and its attachments for presentation in accordance with a previously described embodiment of the invention. In another embodiment the handheld device 100 forwards the entire e-mail, including text of the e-mail and the pointers to attachments, to the communication device 300
20 of a presentation unit 380. Then the communication device 300 manages the presentation of the e-mail and its attachment. If an e-mail only is in plain text and the presentation unit is a printer 380 the communication device 300 does not need to utilize the print service
25 previously described because most printers are able to print plain text without having the files converted to another format.

To ensure security HTTPS or other secure channels can be used for the transfer of the attachments or the e-
30 mails.

In Fig. 13 there is shown a flowchart of one embodiment for printing e-mails and attachments of the e-mail from a handheld device, e.g. a cellular telephone or a PDA. A user accesses the information service provider
35 providing the user with an e-mail service and downloads a new e-mail text to the telephone, step 1002.

Then the user is able to read the text of the e-mail and to determine whether to print the text of the e-mail and possible attachments, step 1004. If the user does not want to start the print operation, the user returns to the e-mail interface of the telephone, step 1002, and is able to download the next e-mail. However, if the user wants to print, then the user selects "Send Mail" in a menu or by pushing a button, step 1006.

Then the user selects Bluetooth as transfer method, step 1008. The telephone broadcasts a request for identification to all bluetooth-enabled devices that are within reach of the bluetooth signal. If no bluetooth-enabled devices are responding to the request the telephone returns to the e-mail interface, step 1002. If there are one or a plurality of responses to the request the telephone have to check whether the responding devices are printers or not, step 1012. If no one of the responding devices are printers then the telephone returns to the e-mail interface, step 1002. If one or more devices responding are printers, then the user is able to select one of them and initiate data transfer, step 1014.

The communication device of the printer receives the data including the text of the e-mail and pointers to possible attachemnts. The communication device then orders the printer to print the text of the e-mail, step 1016. In one embodiment of the invention the telephone is arranged to make it possible for the user to select between a number of presentations, e.g. presentation of the e-mail text and all attachments, only the attachments, only the e-mail text, specific attachments, etc.

Then the communication device checks if the received data included any pointers to attachments, step 1018. If no pointers are present the print job is finished, but if the data included pointers to one or more attachments the communication device downloads/requests them in a

printable format and order the printer to print them,
step 1020. If the pointer of an attachment is pointing to
an attachment that is printable without first being
transformed the communication device downloads it
5 directly, but if the format of the attachment is not
printable without transformation the request is sent to a
print service, as described above, and the print service
is ordered to transform the attachment.

CLAIMS

1. A method in a system for selection and
5 presentation of information, comprising the steps of:
 receiving a presentation unit identification at a
handheld device via a short-range wireless connection
from a communication device for a presentation unit,
 sending a document address from the handheld device
10 via a network to a device that handles presentation
requests,
 receiving said document address and a presentation
unit specification at the device that handles
presentation requests,
15 retrieving, at the device that handles presentation
requests, the document corresponding to said document
address,
 converting, at the device that handles presentation
requests, the retrieved document to a format suitable for
20 the presentation unit,
 sending the converted document from the device that
handles presentation requests via a network to the
communication device for a presentation unit, and
 receiving said converted document at the
25 communication device for a presentation unit.
2. A method according to claim 1, further comprising
the steps of receiving a presentation unit specification
at a handheld device via the short-range wireless
connection from a communication device, and
30 sending said presentation unit specification from
the handheld device via a network to a device that
handles presentation requests.
3. A method according to any one of claim 1 or 2,
wherein said communication device for a presentation unit
35 passes said converted document to a presentation unit
connected to said communication device for a presentation
unit.

4. A method according to any one of claims 1-3, wherein said presentation unit specification at least comprises a presentation address, to which the presentation document can be sent for presentation, and
5 data indicating a format suitable for presentation at the presentation unit.

5. A method according to any one of the preceding claims, wherein the step of converting comprises the steps of:

10 reading the presentation unit specification, and determining the format in which the document is saved,

selecting a conversion method in accordance with the contents of the presentation unit specification and the
15 format in which the document is saved,

converting the document by means of the selected conversion method.

6. A method according to any one of the preceding claims, wherein the presentation address is an e-mail
20 address and wherein the converted document is sent to the presentation unit via an e-mail server.

7. A system for selection and presentation of information, comprising:

a handheld device, enabled to present information
25 retrieved from an information provider on a screen in the handheld device, including:

an I/O-interface for short-range wireless communication with a communication device for a presentation unit,

30 means for receiving a presentation unit identification via said I/O-interface for short-range communication, and

means for sending a document address to a device that handles presentation requests,

35 a device that handles presentation requests, including:

means for receiving a document address,
referring to a document that is to be presented,
from a handheld device,

5 means for receiving a presentation unit
specification,

means for retrieving the document corresponding
to the document address,

10 means for converting the retrieved document to
a format that is suitable for the presentation unit
according to the presentation unit specification,
and

means for sending the converted document to the
presentation address,

15 a communication device for a presentation unit,
including:

an I/O-interface for short-range wireless
communication with a handheld device,

20 means for sending a presentation unit
identification via said I/O-interface for short-
range wireless communication, and

means for receiving information to be presented
by a presentation unit.

8. A system according to claim 7, wherein the
handheld device further includes:

25 means for receiving a presentation unit
specification via the I/O interface for short-range
communication, and

means for sending a received presentation unit
specification to the device that handles presentation
30 requests,

and wherein the communication device further
includes:

means for sending a presentation unit specification
via the I/O interface for short-range communication.

35 9. A system according to any one of claims 7 or 8,
wherein said presentation unit specification at least
comprises a presentation address, to which the

presentation document can be sent for presentation, and data indicating a format suitable for presentation at the presentation unit.

10. A system according to any one of claims 7-9,
5 wherein said means for converting comprises:

a plurality of conversion means, and

means for selecting one conversion means, of the plurality of conversion means, in accordance with the presentation unit specification.

10 11. A system according to claim 10, wherein said means for converting further comprises:

means for determining the format of the document,
and

15 means for interpretation of the format of the document.

12. A system according to any one of claims 7-11, wherein said communication device for a presentation unit is provided with an I/O interface for communication over a network.

20 13. A system according to claim 12, further comprising an e-mail server and wherein the presentation address is an e-mail address.

14. A method for a device that handles presentation requests, comprising the steps of:

25 receiving a document address referring to a document that is to be presented,

receiving a presentation unit specification,

retrieving the document corresponding to the document address,

30 converting the retrieved document to a format that is suitable for the presentation unit, and
sending the converted document.

15. A method according to claim 14, wherein said presentation unit specification at least comprises a
35 presentation address, to which the presentation document can be sent for presentation, and data indicating a

format suitable for presentation at the presentation unit.

16. A method according to any one of claims 14-15, wherein the document address and the presentation unit specification is received via a network.

17. A method according to any one of claims 14-16, wherein the step of converting comprises the steps of reading the presentation unit specification, determining the format in which the document is saved,

selecting a conversion method in accordance with the contents of the presentation unit specification and the format in which the document is saved, and converting the document by means of the selected conversion method.

18. A method according to any one of claims 14-17, wherein the retrieved document is converted to a format suitable for printing by means of a printer.

19. A method according to any one of claims 14-18, wherein the converted document is sent over a network to be presented by means of a presentation unit.

20. A method according to claim 19, wherein the converted document is sent by e-mail, addressed to the presentation unit.

21. A method according to claim 19, wherein the converted document is sent to a presentation unit.

22. A device that handles presentation requests, comprising:

means for receiving a document address referring to a document that is to be presented,

means for receiving a presentation unit specification,

means for retrieving the document corresponding to the document address,

means for converting the retrieved document to a format that is suitable for the presentation unit according to the presentation unit specification, and

means for sending the converted document to the presentation unit.

23. A device according to claim 22, wherein said presentation unit specification at least comprises a presentation address, to which the presentation document can be sent for presentation, and data indicating a format suitable for presentation at the presentation unit.

24. A device according to claim 22 or 23, wherein said means for receiving a document address and said means for receiving a presentation unit specification are arranged for receiving the address and the specification over a network.

25. A device according to any one of claims 22-24, wherein said means for converting comprises:

a plurality of conversion means, and
means for selecting one conversion means, of the plurality of conversion means, in accordance with the presentation unit specification.

26. A device according to claim 25, wherein said means for converting further comprises:

means for determining the format of the document, and

means for interpretation of the format of the document.

27. A device according to any one of claims 22-26, wherein said means for receiving the document address and said means for receiving a presentation unit specification are arranged to receive the data via a network, and

said means for sending the converted document is arranged to send the data via a network.

28. A computer program product directly loadable into the memory of a digital computer, comprising software code portions for performing the steps of claim 14 when said product is run on a computer.

29. A method for a communication device for a presentation unit, said method comprising the steps of:

 sending an identification, and
 receiving, after sending the identification, a
5 document for presentation by the presentation unit.

30. The method according to claim 29, further comprising the steps of:

 receiving a request of a presentation unit specification,
10 sending, after receiving the request, the requested specification, and
 receiving, after sending the requested specification, a document for presentation by the presentation unit.

15 31. A method according to claim 29 or 30, wherein the received request is received over a short-range wireless connection, and wherein the requested identification is sent via a short-range wireless connection.

20 32. A method according to any one of claims 29-31, wherein the received document is received via a network.

 33. A method according to any one of claims 29-32, further comprising the step of making the presentation unit present the received document.

25 34. A method according to claim 33, wherein the step of making the presentation unit present the received document comprises passing the document to a printout process in a printer.

 35. A method according to any one of claims 29-34, comprising the step of checking a mailbox for
30 presentation documents at predetermined time intervals.

36. A communication device for a presentation unit, comprising:

 an I/O-interface for short-range wireless
35 communication,

means for sending a presentation unit identification via said I/O-interface for short-range wireless communication,

5 means for receiving information to be presented by a presentation unit, and

means for making the presentation unit present the received information.

37. A device according to claim 36, further comprising:

10 means for receiving a request regarding a presentation unit specification via said I/O-interface for short-range wireless communication,

means for sending the presentation unit specification,

15 38. A device according to any one of claims 36-37, further comprising an I/O interface for a network connection.

39. A device according to any one of claims 36-38, wherein the presentation unit is a printer.

20 40. A method for a handheld device, enabled to present information retrieved from an information provider on a display in the handheld device, for presenting information on a presentation unit separate from the handheld unit, said method comprising the steps of:
25

receiving a presentation unit identification via a short-range wireless connection from a communication device for the presentation unit, and

30 sending an address of a selected information document to a device handling presentation requests.

41. A method according to claim 40, further comprising the steps of:

35 receiving a presentation unit specification via the short-range wireless connection from the communication device, and

sending the presentation unit specification to the device handling presentation requests.

42. A method according to claim 41, further comprising the step of requesting a presentation unit specification via the short-range wireless connection as a response to a selection of a identified presentation unit.

43. A method according to any one of claims 40-42, further comprising the step of broadcasting an identity request via the short-range wireless connection for identification of presentation units nearby.

44. A handheld device, enabled to present information retrieved from an information provider on a display in the handheld device, for presenting information on a presentation unit separate from the handheld unit, the handheld device comprising:

an I/O-interface for short-range communication, means for receiving a presentation unit identification via said I/O-interface for short-range communication, .

means for selecting the information accessible from the information provider to be presented on the presentation unit, and


means for sending a request for presenting the information on the presentation unit.

45. A handheld device according to claim 44, further comprising:

means for receiving a presentation unit specification via said I/O-interface for short-range communication, and

means for sending the presentation unit specification.

46. A handheld device according to any one of claims 44-45, further comprising means for broadcasting an identity request via said I/O interface for short-range communication.



1/13




FIG 1




FIG 2




FIG 3

4/13




FIG 4




FIG 5

6/13




FIG 6

7/13




FIG 7a




FIG 7b

8/13




FIG 8

9/13




FIG 9

10/13




FIG 10a




FIG 10b





FIG 11



13/13




FIG. 13

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/02517

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G06F 3/00, G06F 17/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0869688 A2 (NOKIA MOBILE PHONES LTD), 7 October 1998 (07.10.98), abstract	29-35
A	--	1-28, 36-46
X	US 4943994 A (H.OHTSUKA ET AL), 24 July 1990 (24.07.90), abstract	29-35
A	--	1-28, 36-46
A	Patent Abstracts of Japan, abstract of JP 10-126347 A (CANON INC), 15 May 1998 (15.05.98)	1-46

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 March 2001

Date of mailing of the international search report

23 -03- 2001

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Jan Silfverling/LR

Telephone No. +46 8 782 25 00

Form PCT/ISA 210 (second sheet) July 2000

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/SE 00/02517

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
EP	0869688	A2	07/10/98	FI 971386 A	05/10/98
US	4943994	A	24/07/90	DE 3856152 D,T	05/11/98
				EP 0314122 A	03/05/89
				EP 0602010 A,B	15/06/94
				JP 1117487 A	10/05/89
				JP 2038685 C	28/03/96
				JP 7071272 B	31/07/95
				KR 9201008 B	01/02/92
				JP 1117488 A	10/05/89
				JP 1117489 A	10/05/89
				JP 1117490 A	10/05/89
				JP 1122284 A	15/05/89